


Available from Woertz-USA




The Comat CMS-10 SMS relay is a remote control and messaging system.

- Six digital inputs and four relay outputs with

alternating contacts are monitored by means of a SMS (Short Message System) via a mobile telephone network* (SIM card determines the provider).

- The device's own phone book saves up to 50 mobile phone numbers of the receivers.
- Each status change at the input sends a pre-defined message by SMS to the selective receivers.
- Outputs can be switched on and off by means of a predefined message by SMS.
- **FREE** – Simple-to-use programming software template (can be downloaded from www.comat.ch)



Woertz-USA offers one of the smallest Din Rail mountable relays, Optocouplers and signal conditioners.

At only 5.08mm wide, Woertz's Snapline POWER relays are

offered with a variety of coil voltages 5VDC, 12VDC, 24VDC, 115VAC and 230VAC. The contact is rated up to 6 Amps switching AC and DC voltage (resistive loads).

Solid state "Optocouplers" are also offered in the Snap-line series to switch AC and DC loads. A variety of input voltages are offered TTL, 5VDC, 12VDC, 115VAC, 230VAC...and more. A maximum switching current is 7Amps. HIGH Speed Optocouplers are also available Please visit www.woertz-usa.com to download spec sheets or request a full line catalog.

Integra Polycarbonate Enclosures Offers impact resistance of over 900 lb/in.!



FYI: Fiberglass boxes typically have an impact resistance of less than 220 lb/in...and they are difficult to work with.

Integra's


polycarbonate box is not like anyone else's. Their superior design provides an enclosure that is durable, seals tight, supports component installation, and looks great! A variety of sizes are available and are Nema 4X or better. Please call to request a catalog. We have many samples at our office for your review.

Pfannenberg offers a compact, side mount



air conditioner for small enclosures or hot spot cooling for larger enclosures. With dimensions of only 20.25"x10"x11" (HxWxD) this compact unit offers 2000-3000BTU of cooling capacity. This unit is available as a Nema type 12, 3R, 4/4X; 115 and 230V.

Pfannenberg's New 4th Generation Filter Fans are Nema Type 12. Features include a




patented "click & fit" installation (no hardware); a special fluted filter which increases time between maintenance by 3X and allows for

greater CFM...and more.

There are 8 models that range from 4" to 12". Reverse flow models also available.

Other thermal management products:

- Heater fans
- Air-water heat exchangers
- Chillers



Schaefer's Electrical Enclosures offers very competitive pricing on standard mild steel and stainless steel Industrial enclosures. They can provide custom enclosures, any quantity, with a 2-4 week turn-around.

We welcome the opportunity to quote on your next enclosure project.

New Lines:



Industries smallest sensor

Model: C-120x

Senva - Offering Current Sensors

The C-234x Split core Analog series offers a selectable current range 0-30, 60, 120Amps. Sensor output types are 0-5V; 0-10V or 4-20mA. A command relay can be snapped onto

the C-234x series to get load control and status in a compact device.

Please visit www.gbuelectrotech.com to down-load a complete Senva catalog.

Champ Engineering



CTC2104 10.4" VGA Touch Panel USB:

800x600 pixels and 1024x768; Power 12VDC/1.0Amps; Video system: PAL/NTSC; NEMA 12



Conductivity Meters to measure the conductivity of liquids when a user supplied cell (sensor) is connected to it. Used for water quality monitoring, filter or system leak detection, moisture detection in soils, quality assurance...and more

Please visit www.gbuelectrotech.com to down load a complete spec sheet.